

# BATES® HTR-4

## *An All-Temperature Release Coating*

A semi-firm, highly scrape-able release coating intended for a wide range of applications, including high temperature. BATES HTR-4 provides durable protection against highly active compounds such as finishes, adhesives and resins.

### THE BENEFITS OF BATES HTR-4

- Provides durable protection in production and finishing areas where heavy, stubborn build-up occurs
- Reduces clean-up time
- Regular application prevents harsh cleaning that abuses and deteriorates equipment

### APPLICATION, COVERAGE & USE

- For any temperature application - Up to 370°F/188°C
- Easily brushed, wiped or sprayed on.

### PROPERTIES & STORAGE

- BATES HTR-4 should be stored in ambient temperatures. Avoid high heat, open flames, direct sunlight and freezing temperatures.

### DIRECTIONS FOR USE

Apply BATES HTR-4 to any non-porous surface that collects overspray, dripping, or other accumulation of unwanted compounds. Apply below 200°F/95°C for best film formation. Use to protect spray booths, presses, compression molders, high frequency gluing machines and other areas from unwanted build-up.

### PURCHASE OPTIONS

- Available Quantities:
  - 55-gallon drum
  - 5-gallon pail
- **Pricing information:** Please refer to the **U-C Coatings Product Price List (US & Canada)**
- **Place an order:**
  - US/CN Toll Free: **1-888-END-COAT**
  - Outside US/CN: **+1 (716) 833-9366**
  - On the Web: **www.uccoatings.com**



**U·C COATINGS CORPORATION**

*"We're more than just end coatings"*

PO Box 1066  
Buffalo, NY 14215, USA  
tel: 1 (716) 833-9366  
fax: 1 (716) 833-0120  
**1-888-END-COAT**  
[www.uccoatings.com](http://www.uccoatings.com)