

## SAFETY DATA SHEET

**PRODUCT NAME: UC TRUCK DECK COATING**

DATE PREPARED: January 8, 2019

### 1. IDENTIFICATION

Identity (as used on label and listings): BATES® UNDER-SEAL TRUCK DECK COATING

Chemical Family/Specific Type: Water-based asphalt coating

Recommended Use: Sealer coating for truck floors and decks

<u>Manufacturer:</u>	U•C Coatings, LLC	Telephone Number:	716-833-9366
	P.O. Box 1066	Fax Number:	716-833-0120
	Buffalo, NY 14215 U.S.A.	Emergency Telephone No.:	716-833-9366

### 2. HAZARD(S) IDENTIFICATION

**Health Hazards:**

Ingestion	Category 4
Skin irritation	Category 3
Eye irritation	Category 2B

Hazard Pictogram:

**Signal Word:** **WARNING**
**Hazard Statements:** Physical Hazards: None

Health Hazards: H316 Causes mild skin irritation  
H320 Causes eye irritation

Environmental Hazards: This substance is not expected to be toxic to aquatic organisms. However, it is still advised that this substance does not enter the environment.

**Precautionary Statements:**

<u>Prevention:</u>	P264	Wash affected areas thoroughly after handling
	P280	Wear protective gloves and eye protection
<u>Response:</u>	P331	IF SWALLOWED: Rinse mouth. Drink large amounts of water. Do not induce vomiting (aspiration hazard). Seek medical help immediately for ingestion of wax and soap.
	P302	IF ON SKIN: Wash with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.
	P305	IF IN EYES: Flush eyes immediately with large amounts of water, using soap if possible. Remove contact lenses if present and easy to do. If irritation continues, seek medical attention.
<u>Storage:</u>		Store above 5°C / 40°F. Product can be damaged by freezing.
<u>Disposal:</u>	P501	Dispose of contents/container in accordance with local, regional and federal regulations.

**NFPA/HMIS Ratings (scale 0-4):** HEALTH = 1    FIRE = 1    REACTIVITY = 0    (0 = Minimal Hazard    4 = Severe Hazard)  
Protective Equipment: Protective gloves and eye protection

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Characterization: Mixture / water-based asphalt coating

<u>Main Ingredient:</u>	Acrylic Polymer Emulsion	<u>CAS No.</u>	8052-42-4	40-50%
<u>Classified Ingredients:</u>	None			

*No other classified ingredients are present which contribute to this product's GHS Hazard Categorization as prescribed by OSHA's Hazard Communication 29 CFR 1910.1200*

**PRODUCT NAME: BATES® UNDER-SEAL TRUCK DECK COATING****4. FIRST AID MEASURES**

- After Eye Contact: Flush eyes immediately with large amounts of water, using soap if possible. Remove contact lenses if present and easy to do. If irritation continues, seek medical attention.
- After Skin Contact: Wash with plenty of soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.
- After Swallowing: Rinse mouth. Drink large amounts of water. Do not induce vomiting (aspiration hazard). Seek medical help immediately for ingestion of wax and soap.
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed: No further relevant information available.

**5. FIRE FIGHTING MEASURES**

- Extinguishing Media: Spray with dry chemical, carbon dioxide (CO<sub>2</sub>), foam.
- Other Fire or Combustion Hazards: Incomplete combustion can produce carbon monoxide and carbon dioxide.
- Fire Fighting Instructions: Avoid breathing smoke and vapor.
- Fire Fighting Equipment: Self-contained breathing apparatus and protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal Protection: Wear protective gloves and eye protection plus rubber boots when containing large spills.
- Precautions: Do not allow to enter sewers / surface or ground water.
- Containment and Clean-up: Large spills: contain with dikes, collect, and filter for reuse.  
Small spills: collect or absorb with oil absorbent pads.  
Clean contaminated areas with soap and water. All spill response and disposal should be carried out in accordance with local, regional and federal regulations.

**7. HANDLING AND STORAGE**

- General: Keep containers closed to minimize evaporation and skin formation.
- Handling: Use normal precautions and protective equipment to avoid exposure to eyes and skin.
- Storage: Store at ambient temperature, above 5°C / 40°F. Product can be damaged by freezing.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Ventilation: Good ventilation in work area, atmospheric pressure.
- Personal Protection: Eyes: safety glasses or splash goggles  
Hands: protective gloves  
Other: synthetic apron for cleanliness
- Exposure guidelines: Asphalt exposure TWA 0.5 mg/m<sup>3</sup> per ACGIH, TLV guidelines  
Ceiling 5mg/m<sup>3</sup>, fumes 15 minutes per NIOSH, IDLH guidelines

**9. PHYSICAL & CHEMICAL CHARACTERISTICS**

- Physical State: Liquid Odor: slight odor
- Appearance/Color: Dark brown/green liquid
- Viscosity: Typical 400 Cps at 25°C / 77°F (Ford cup)
- Flash Point: No flash - boils at 100°C / 212°F Auto ignition temperature: n/a
- Boiling Point: 100°C / 212°F Melting/Freezing Point: 0°C / 32°F

**PRODUCT NAME: BATES® UNDER-SEAL TRUCK DECK COATING****9. PHYSICAL & CHEMICAL CHARACTERISTICS (continued)**

Vapor Pressure: no information available      Specific Gravity: 1.04 typical  
Vapor Density (air = 1): no information available      Evaporation Rate (butyl acetate = 1): no information available  
Solubility In Water: no information available  
Volatile Organic Compounds: no information available  
Volatile Hazardous Air Pollutants: no information available  
Organic Hazardous Air Pollutant Solvents: no information available

**10. STABILITY AND REACTIVITY**

Reactivity: No data available.  
Chemical Stability: Stable under normal temperatures and conditions.  
Possibility of Hazardous Reactions: Under normal temperatures and conditions, hazardous reactions will not occur.  
Conditions to Avoid: Extreme temperatures and direct sunlight.  
Incompatible Materials: Unknown.  
Hazardous Decomposition Products: Under normal temperatures and conditions, hazardous decomposition products should not be produced. Burning may produce carbon monoxide and/or carbon dioxide.

**11. TOXICOLOGICAL INFORMATION**

No known health hazard, no data available.

**12. ECOLOGICAL INFORMATION**

No data available.

**13. DISPOSAL CONSIDERATIONS**

Not a hazardous waste. Where recovery and reuse is not possible, dispose of as an industrial waste or by incineration where permitted under local, regional, or federal regulations.

**14. TRANSPORTATION INFORMATION**

ADR/RID: Not regulated  
IMDG: Not regulated  
ICAO/IATA: Not regulated

**15. REGULATORY INFORMATION**

The ingredients in this product are in the TSCA, MITI, AICS, DSL inventories.

**16. OTHER INFORMATION**

This SDS was prepared 8 January 2019.