



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

ANCHORSEAL® is a wax emulsion end sealer that protects freshly cut logs and lumber from damaging end splits while air drying. ANCHORSEAL can be used on hardwood and softwood logs and lumber to protect against degradation.

FEATURES

- Prevents up to 90% of end checks and drying splits
- Can be applied to all species of hardwood or softwood
- Helps prevent blue stain and sapstain caused by damaging fungi
- Water based, non-toxic formula
- Available in clear or more than 35 colors
- Winterized formulas available

PACKAGING SIZES

1 Quart Can | 1 Gallon Can | 5 Gallon Pail
55 Gallon Drum | 275 Gallon Tote

FREIGHT CLASS

55

TYPICAL PHYSICAL CHARACTERISTICS

Color	Viscous white liquid, dries translucent
pH	8-9
lbs/gal	7.9
Specific Gravity	0.95
Viscosity	4,000 cps
Application Temp.	50°F - 90°F (10°C - 32.2°C)
Odor	Nil

SURFACE PREPARATION

All areas to be coated should be clear of dirt and debris.

APPLICATION

- Apply ANCHORSEAL using a brush, roller or sprayer until it begins to drip slightly.
- For optimal coverage, use a gas engine, electric, air operated or backpack sprayer from U-C Coatings.
- If using spray equipment other than those sold by U-C Coatings, use 0.21"/0.55 mm tip or larger.
- Logs larger than 24"/60 cm in diameter will require a heavier coating, or two coats must be applied within a 15 minute period.

COVERAGE

- 100 sq. ft./gallon, depending on application method and wood species.

CLEANUP & STORAGE

- Clean application equipment using hot soapy water.
- Store unused ANCHORSEAL above 50°F/10°C to prevent freezing. Winterized formulas will protect against freeze damage.

PRECAUTIONS

- Contains no toxic or hazardous materials
- Safety Precautions
 - Wear vinyl gloves and eye protection.
 - Avoid breathing in spray. If inhaled, move to fresh air.
 - Avoid contact with eyes. If splashed into eyes, rinse with clean water for 15 minutes.
 - If skin irritation occurs, wash area with soap and water.
 - If accidentally ingested, immediately drink 2 glasses of water and contact a physician. Do not induce vomiting.
 - In case of accidental overexposure, seek medical help.

U·C COATINGS

WOOD PROTECTION PRODUCTS

Manufactured by U-C Coatings, LLC
P.O. Box 1066 | Buffalo, NY 14215 USA
(716) 833-9366 | sales@uccoatings.com | www.uccoatings.com

"ANCHORSEAL" is a registered trademark of U-C Coatings, LLC.