

# GEMPAINT\*PLUS

LUMBER END PAINT

## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

GEMPAINT\*PLUS is a premium water based paint developed specifically for application on the ends of lumber bundles. GEMPAINT\*PLUS is an ultra-pigmented paint that can be applied to green, kiln-dried or air-dried hardwood or softwood lumber bundles.

### FEATURES

- Enhances appearance of lumber bundles
- Ultra-pigmented, water based, non-toxic paint
- Superior representation of company brand
- Apply to lumber ends to identify grade or species
- Available in more than 40 standard and custom colors
- Can be applied to all hardwood and softwood species

### PACKAGING SIZES

5 Gallon Pail | 55 Gallon Drum | 275 Gallon Tote

### FREIGHT CLASS

55

### TYPICAL PHYSICAL CHARACTERISTICS

Color	Viscous, highly pigmented liquid
pH	8.5 - 9.5
lbs/gal	8.4
Solvents	Menthol (winterized version only)
Specific Gravity	1.01
Viscosity	6,000 cps
Application Temp.	50°F - 90°F (10°C - 32.2°C)
Odor	Nil

### SURFACE PREPARATION

- All surfaces to be coated should be clear of dirt and debris.

### APPLICATION

- Apply GEMPAINT using a brush, roller or sprayer. Ensure the area is properly ventilated.
- For optimal coverage, use an electric, air operated or pressure pot sprayer from U-C Coatings.
- If using spray equipment other than those sold by U-C Coatings, use 0.21"/0.55 mm tip or larger.
- Apply GEMPAINT\*PLUS using smooth, even strokes to ensure optimal coverage on bundle ends and stencils.

### COVERAGE

- 150-200 sq. ft./gallon, depending on application method and wood species.

### CLEANUP & STORAGE

- Clean application equipment using hot soapy water.
- Store GEMPAINT\*PLUS in a temperature-controlled area between 50°F/10°C and 95°F/35°F. Winterized formulas will protect against freeze damage.

### PRECAUTIONS

- Contains no toxic or hazardous materials
- Safety Precautions
  - Wear vinyl glove and eye protection. In confined areas, proper breathing apparatus is required.
  - Avoid breathing in spray. If inhaled, move to fresh air.
  - Avoid contact with eyes. If splashed into eyes, rinse with clean water for 15 minutes.
  - If skin irritation occurs, wash area with soap and water.
  - If accidentally ingested, immediately drink 2 glasses of water and contact a physician. Do not induce vomiting.
  - In case of accidental overexposure, seek medical help.

# U·C COATINGS

WOOD PROTECTION PRODUCTS

Manufactured by U-C Coatings, LLC  
P.O. Box 1066 | Buffalo, NY 14215 USA  
(716) 833-9366 | sales@uccoatings.com | www.uccoatings.com

"GEMPAINT" is a registered trademark of U-C Coatings, LLC.